

PRODUCT DATA SHEET

R2132UA FUEL WATER SEPARATOR KIT

Solution for inboard & outboard engine applications

PRODUCT SNAPSHOT

UNIVERSAL FUEL ASSEMBLY

Micron Rating:

R2132P - 18 micron (nominal)

Max Flow Rate:

40-45 litres per hour (nominal)

Fuel Line Pressure:

Not to exceed 206kPa/30psi

Filter Replacement:

Recommended filter change period is when filter causes starvation or every 100 hours.









Applications:

- Suitable for Diesel, Petrol and Pre-mix fuels.
- Can be used on inboard and outboard engines.
- Can be the only filter fitted, or mounted downstream or before existing fuel filter.
- Will not remove oil from 2 stroke mixes where correct miscibility has been achieved.

Specifications:

- Water resistant silicone coated filter media provides maximum efficiency, life and flow for all fuels.
- Cast alloy head assembly.
- Bleed screw provided at the highest point of housing.
- Simple thumb screws.

Fittings & Accessories to suit R2132UA

Product Image / Description	Product Image / Description	Product Image / Description
 <p>MS4021 1/4" BSP Male 1/2" - 20 UNF Male</p>	 <p>MS4022 6mm (1/4") Industrial Hose Tail 1/2" - 20 UNF Male Coupling</p>	 <p>MS4023 8mm (5/16") Industrial Hose Tail 1/2" - 20 UNF Male Coupling</p>
 <p>MS4024 10mm (3/8") Industrial Hose Tail 1/2" - 20 UNF Male Coupling</p>	 <p>FH9747 Replacement Nylon Bowl</p>	 <p>R2132P Replacement Cartridge</p>